

FRESNEL LED 300 SERIES

CRI>95 / TLCI>90

LED PRODUCT

Replaceable LED module with high efficiency, long life, DMX function, available in two different white temperatures like 3150K and 6000K, high CRI >95 (rendering color performance index), TLCI >90 (Television Lighting Consistency Index). Available in three different versions, Fresnel **LED 300 PLUS**, with DMX control, motorized Zoom and manual high precision potentiometer to adjust the dimmer from 0 to 100%. **Studio LED 300 DMX**, with DMX control and manual Zoom. Fresnel **LED 300 Base**, with manual high precision potentiometer to adjust the dimmer from 0 to 100%. The control by DMX allows the coordination with any other device, avoiding the use of traditional dimmer and dedicated lines. It is possible to adjust manually the intensity of the outgoing light by an integrated rotating potentiometer on the spotlight. The dimmer has a soft and linear setting from 0 to 100% without any flickering.



PRODUCT SPECS Neutrik XLR 5P in & out / Neutrik Powercon in & out

cod.	Volt	Control	Power	DMX Channels	Light Color	Beam Angle	Max Noise	Zoom
SPTF-Z300950DD-WW	230Vac	DMX-RDM	300W	3	3150K	9°÷50°	0÷8 dB	Motorized
SPTF-Z300950DD-W	230Vac	DMX-RDM	300W	3	6000K	9°÷50°	0÷8 dB	Motorized
SPTF-300950DD-WW	230Vac	DMX-RDM	300W	2	3150K	9°÷50°	0÷8 dB	Manual
SPTF-300950DD-W	230Vac	DMX-RDM	300W	2	6000K	9°÷50°	0÷8 dB	Manual
SPTF-300950D-WW	230Vac	Manual Dim.	300W	--	3150K	9°÷50°	8 dB	Manual
SPTF-300950D-W	230Vac	Manual Dim.	300W	--	6000K	9°÷50°	8 dB	Manual

ACCESSORIES

cod.	Description	
AC210	Barndoor 4 leaves on a rotating base	optional
AC180	Filter frame	1 included
AC299	50 mm aluminium coupler max load 100 kg	optional
904PR	safety chain, length 75cm, ø 6mm with carabine hook	optional

