

FRESNEL 600 CCT

TUNABLE WHITE CRI>95 / TLCI>90

Replaceable LED module with high efficiency, long life, DMX and digital display control function, tunable white from 2800K to 6500K, high CRI>95, TLCI>90, motorized or manual adjustable zoom from 7° to 55°. The control by DMX Allows the coordinations with any other device, avoiding the use traditional dimmer dedicated lines. The dimmer has a soft and linear setting from 0 to 100% without any flickering.



PRODUCT SPECS Neutrik XLR 5P in & out / Neutrik Powercon in & out

cod.	Volt	Control	Power	DMX Channels	Light Color	Beam Angle	Max Noise	Zoom
SPTF-Z6000755-CCT	230Vac	DMX-RDM	300+300W	4 / 6	2800K-6500K	7°÷55°	10 dB	Motorized
SPTF-6000755-CCT	230Vac	DMX-RDM	300+300W	3 / 4	2800K-6500K	7°÷55°	10 dB	Manual

ACCESSORIES

cod.	Description	
AC1086	Barndoor 4 leaves on a rotating base	optional
AC187	Filter frame	1 included
AC299	50 mm aluminium coupler max load 100 kg	optional
904PR	safety chain, length 75cm, ø 6mm with carabine hook	optional

