

# FRESNEL 450 RGBW

CRI>95 / TLCI>90



Replaceable LED module with high efficiency, long life, DMX and digital display control function, RGBW color mixing, high CRI>95, TLCI>90, motorized or manual adjustable zoom from 7° to 56°. The control by DMX Allows the coordinations with any other device, avoiding the use traditional dimmer dedicated lines. The dimmer has a soft and linear setting from 0 to 100% without any flickering.

LED PRODUCT

**PRODUCT SPECS** Neutrik XLR 5P in & out / Neutrik Powercon in & out

cod.	Volt	Control	Power	DMX Channels	Light Color	Beam Angle	Max Noise	Zoom
<b>SPTF-Z4500755-RGBW</b>	230Vac	DMX-RDM	450W	7	RGBW	7° ÷ 56°	10 dB	Motorized
<b>SPTF-4500755-RGBW</b>	230Vac	DMX-RDM	450W	6	RGBW	7° ÷ 56°	10 dB	Manual

**ACCESSORIES**

cod.	Description	
<b>AC1086</b>	Barndoor 4 leaves on a rotating base	optional
<b>AC187</b>	Filter frame	1 included
<b>AC299</b>	50 mm aluminium coupler max load 100 kg	optional
<b>904PR</b>	safety chain, length 75cm, ø 6mm with carabine hook	optional

