

# FRESNEL 160 WHITE SERIES

CRI>95 / TLCI>90



Replaceable LED module with high efficiency, long life, RDM / DMX function, available in two different white temperatures like 3150K and 5600K, high CRI >95 (rendering color performance index), TLCI >90 (Television Lighting Consistency Index), motorized adjustable zoom from 14° to 71°. Adjustable light output frequency rate. The control by DMX allows the coordination with any other device, avoiding the use of traditional dimmer and dedicated lines. It is possible to adjust manually the intensity of the outgoing light by an integrated rotating potentiometer on the spotlight. The dimmer has a soft and linear setting from 0 to 100% without any flickering.

LED PRODUCT

**PRODUCT SPECS** Neutrik XLR 5P in & out / Neutrik Powercon in & out

cod.	Volt	Control	Power	DMX Channels	Light Color	Beam Angle	Max Noise	Zoom
<b>SPTF-2001066LD-WW</b>	230Vac	DMX-RDM	160W	4	3150K	14°÷71°	0÷8 dB	Motorized
<b>SPTF-2001066LD-W</b>	230Vac	DMX-RDM	160W	4	5600K	14°÷71°	0÷8 dB	Motorized
<b>SPTF-2001065LD-WW</b>	230Vac	DMX-RDM	160W	4	3150K	14°÷71°	0÷8 dB	Manual
<b>SPTF-2001065LD-W</b>	230Vac	DMX-RDM	160W	4	5600K	14°÷71°	0÷8 dB	Manual

**ACCESSORIES**

cod.	Description	
<b>PR2001660</b>	Barndoor 4 leaves on a rotating base	optional
<b>AC181</b>	Filter frame	1 included
<b>AC299</b>	50 mm aluminium coupler max load 100 kg	optional
<b>904PR</b>	safety chain, length 75cm, ø 6mm with carabine hook	optional



cod. **SPTF2001066LD**  
**MOTORIZED ZOOM**

with **POLE OPERATING YOKE**  
cod. **YPF-2001066LD-WW**  
**YPF-2001066LD-W**

with **MOTORIZED DMX YOKE**  
cod. **YSF-2001066LD-WW**  
**YSF-2001066LD-W**



cod. **SPTF2001065LD**  
**MANUAL ZOOM**

