

FRESNEL 110 SERIES

CRI>95 / TLCI>90

LED PRODUCT

Replaceable LED module with high efficiency, long life, heatsink without forced cooling 0 dB, available in two different white temperatures like 3150K and 5600K, high CRI >95 (rendering color performance index), TLCI >90 (Television Lighting Consistency Index), manually adjustable zoom from 9° to 57°. Digital display with function control possibilities and DMX addressing. The control by DMX allows the coordination with any other device, avoiding the use of traditional dimmer and dedicated lines. It is possible to adjust manually the intensity of the outgoing light by an integrated rotating potentiometer on the spotlight. The dimmer has a soft and linear setting from 0 to 100% without any flickering.



PRODUCT SPECS Neutrik XLR 5P in & out / Neutrik Powercon in & out

cod.	Volt	Control	Power	DMX Channels	Light Color	Beam Angle	Max Noise	Zoom
SPTF1801064LD-WW	230Vac	DMX-RDM	110W	2	3150K	9°÷57°	0 dB	Manual
SPTF1801064LD-W	230Vac	DMX-RDM	110W	2	5600K	9°÷57°	0 dB	Manual

ACCESSORIES

cod.	Description	
AC210	Barndoor 4 leaves on a rotating base	optional
AC180	Filter frame	1 included
AC299	50 mm aluminium coupler max load 100 kg	optional
904PR	safety chain, length 75cm, ø 6mm with carabine hook	optional



with
POLE OPERATING YOKE

cod.
YPF-1801064LD-WW
YPF-1801064LD-W



with
MOTORIZED DMX YOKE

cod.
YSF-1801064LD-WW
YSF-1801064LD-W

