

# DALI LED SERIES

CRI>95 / TLCI>90



Replaceable LED module high efficiency, long life, available in three different temperatures of white, 3000K, 4000K and 5700K, high CRI> 95, manually adjustable zoom 7° to 48°. Dimmable through DMX signal, integrated rotary potentiometer on the back for 55W version and cut-phase dimmable for 35W version. More performance a 300W tungsten lamp with only 60W power consumption. The master dimmer has a soft and continuous adjustment from 5 to 100%.

### Available in different body colors

Black White Silver



### PRODUCT SPECS

Neutrik XLR 5P in & out / Neutrik Powercon in & out

cod.	Volt	Control	Power	DMX Channels	Light Color	Beam Angle	Max Noise	Zoom
<b>SPTD7055-WW</b>	230Vac	DMX-RDM	55W	2	3000K	7°÷48°	0÷8 dB	Manual
<b>SPTD7055-NW</b>	230Vac	DMX-RDM	55W	2	4000K	7°÷48°	0÷8 dB	Manual
<b>SPTD7055-W</b>	230Vac	DMX-RDM	55W	2	5700K	7°÷48°	0÷8 dB	Manual
<b>SPTD7055P-WW</b>	230Vac	Manual DIM.	55W	--	3000K	7°÷48°	8 dB	Manual
<b>SPTD7055P-NW</b>	230Vac	Manual DIM.	55W	--	4000K	7°÷48°	8 dB	Manual
<b>SPTD7055P-W</b>	230Vac	Manual DIM.	55W	--	5700K	7°÷48°	8 dB	Manual
<b>SPTD7033-WW</b>	230Vac	Cut-Phase Dim.	35W	--	3000K	7°÷48°	8 dB	Manual
<b>SPTD7033-NW</b>	230Vac	Cut-Phase Dim.	35W	--	4000K	7°÷48°	8 dB	Manual
<b>SPTD7033-W</b>	230Vac	Cut-Phase Dim.	35W	--	5700K	7°÷48°	8 dB	Manual

### ACCESSORIES

cod.	Description	
<b>PR8060</b>	Barndoor 4 leaves on a rotating base	optional
<b>AC182</b>	Filter frame	1 included
<b>AC299</b>	50 mm aluminium coupler max load 100 kg	optional
<b>904PR</b>	safety chain, length 75cm, ø 6mm with carabine hook	optional

