

MONOBLOQ



MONOBLOQ

Gold
For 10 mm cable

Art. Nr. 15305100010



MONOBLOQ

Gold
For 8 mm cable

Art. Nr. 15305100008



MONOBLOQ

Black
For 10 mm cable

Art. Nr. 1530510001095



MONOBLOQ

Black
For 8 mm cable

Art. Nr. 1530510000895



8 MM STEEL ROPE 10 M

Art. Nr. 152050810000



10 MM STEEL ROPE 10 M

Art. Nr. 152051010000



SAFE



QUICK ADJUSTMENT



EASY TO HANDLE

For more information:



H.O.F. Alutec
Metallverarbeitungs GmbH & Co. KG
Brookstraße 8
D-49497 Mettingen
P +49 (0) 54 52-97 33-10
sales@h-of.de
www.h-of.de

f i n y
@hofalutec

NO EVOLUTION. A REVOLUTION.



MONOBLOQ.
SAFE.
QUICK ADJUSTMENT.
EASY TO HANDLE.

H^{OF}

MONOBLOQ

IT'S NOT AN EVOLUTION - IT'S A REVOLUTION! WHY?

All you need is a **single fix cable** plus **Monobloq** to create your hanging point. The patented system allows a cable adjustment in seconds and the installation of up to 8 bridles per hour with 2 technicians.

Safe. Quick adjustment. Easy to handle.

HOW DOES MONOBLOQ WORK?

Insert the 8 mm steel rope into the open Monobloq device for 8 mm steel ropes (or the 10 mm steel rope into the open Monobloq device for 10 mm steel ropes).

Once the **steel rope is in the device**, the pressure wedge is placed in the Monobloq body recess and the cover is fixed by **3 fixing screws**. Then the shackle is mounted and gets attached to the structural element.

Once Monobloq is suspended from the shackle, the length of the cable can be adjusted by exerting two-handed effort in the desired direction of travel. To fix the cable at a given point, a manual load must be exerted.

Finally, insert the set screw on the side opposite the load and screw until it is tightened.

Ready for use!



SAFE

The system is patented and flexible hanging points can be positioned appropriately within seconds.



QUICK ADJUSTMENT

Once Monobloq is suspended from the shackle, the length of the cable can be adjusted by exerting two-handed effort in the desired direction of travel.



EASY TO HANDLE

All you need is a suspension rope and the Monobloq to create a flexible hanging point. The patented system allows positioning in seconds and the installation of up to 8 bridles per hour.

