

PROFILE PRO 1000 HALO 20° - 40°

LINEAR PIXEL TO PIXEL CONTROL



Power Supply Fixture voltage depending from the lamp type voltage selected (230/110Vac 50/60Hz), 1000W, for Lamp Halogen 1000W CP70 650W CP24 650W CP23, Socket GX9.5. Manual Zoom 20°÷40°. Profile System four steel shutter blades included. Optional Iris diaphragm Ø 55mm. Optional Gobo holder for Ø 66mm gobo. Colour frame included. Optics system with High efficiency reflector and plano-convex zoom lens Ø120mm and Ø180mm, perfect focus with the same system and adjustment of the softness of the beam boundary. Natural convection cooling 0dB, housing in extruded aluminium and steel plate body. Scratch resistant black epoxy powder paint. Projector can work tilted by +60°/-45°. Weight 15 Kg

TUNGSTEN PRODUCT

PRODUCT SPECS

For lamp Tungsten 1000W - Profile system

cod.	Input	For Lamp	Base	Optical system	Zoom	Focus
TH1257	110V / 230V	1000W	GX9.5	Double condenser	20°÷ 40°	Adjustable

ACCESSORIES

cod.	Description	
508LA	1000W tungsten lamp T19 / GX9.5	optional
AC837	Iris	optional
AC819	Fixed Gobo holder	optional
AC299	50 mm aluminium coupler max load 100 kg	optional
904PR	safety chain, length 75cm, ø 6mm with carabine hook	optional



with
**POLE
OPERATING YOKE**
cod.
YPR-TH1257



with
**MOTORIZED DMX
YOKE**
cod.
YSR-TH1257

